

RJ45 CAT6 8-WIRE PLUG



DESCRIPTION

Connection offers plugs in standard configurations to terminate modular cord cables for patching or workstation applications. Modular cords can be terminated to the exact length needed for more organized installations. The plugs terminate 24 and 26 AWG.

PAIRS	PIN	COLOR CODE
# 1	5 4	WHITE/BLUE BLUE/WHITE
# 2	1 2	WHITE/ORANGE ORANGE/WHITE
# 3	3 6	WHITE/GREEN GREEN/WHITE
# 4	7 8	WHITE/BROWN BROWN/WHITE

Block Housing:	ABS Molding Compound PA-767 94V-O ULE. 46920
Combed Jack Housing:	94V-O Plastic
Contacts:	Phosphor Bronze, 50m inches Gold Over Nickel Plate
Wiring	4 Pairs / 8 Wires AT&T 568B
Categories:	Cat6

SPECIFICATIONS:

Material and Finish:

- Housing: Polycarbonate (PC)
- Contacts: 50um Gold over Nickel Plate (Copper Alloy Selective)

Mechanical:

- Cable-to-Plug: 20lbs min.
- Durability: 750 Cycles Minimum

Electrical:

- Rated Voltage: 30VAC at 1.5 Amps
- Contact Resistance: 10 milliohms maximum
- Dielectric Strength: 1000VAC (RMS)
- Insulation Resistance: 500 Megaohms minimum
- Operating Temperature: -20°C to 80°C

ORDER INFORMATION

P/N	Description
CRJ-8725	RJ45 Cat6 8-Wire Plug