

8 in 1 MPEG-2 AVC SD Encoder



OVERVIEW

8IN1 MPEG-2 SD Encoder supports SD MPEG-2 video and MPEG-1 audio encoding. It has 8×CVBS video, 8 pairs of unbalanced audio input interfaces, and 1×ASI output port. The encoder suits 1U rack and can be configured by front panel LCD and NMS (network management software). Its high-integrated and cost-effective design makes it widely used in varieties of digital distribution systems such as cable TV digital head-end, satellite digital TV broadcasting and terrestrial digital TV, etc.

FEATURE

- MPEG-2 video and MPEG-1 audio encoding
- 8×CVBS video and 8 pairs of unbalanced audio (high-fidelity mono/stereo) input
- Support PAL and NTSC video formats
- Support ASI output
- LCD/Keyboard control by front panel and network management by Ethernet

8 in 1 MPEG-2 AVC SD Encoder

SPECIFICATIONS

Input	Video Signal	8×CVBS, Serial interface, level 1.0 Vp-p
	Audio Signal	8 pairs of unbalanced audio, Serial interface, level 2.0 Vp-p
Video Coding		Comply with ISO11172 (MPEG-1) & ISO13818 (MPEG-2)
		MPEG-2 coding adopt MP@ML (4:2:0)
		MPEG-2 Adaptive Field Frame (AFF)
		MPEG-2 Field-Based (FB)
Resolution	Standard	support 1/2D1, 2/3D1, 3/4D1, 9/16D1
	Format	PAL/NTSC
Audio Coding	Sampling	32KHz, 44.1KHz, 48KHz
	Code Rate	32, 48, 56, 64, 128, 192, 256, 384, 448Kbps
	Property	MPEG-1 Layer2, 1×stereo or dual-channel
Output	1×ASI	1 as mirror, DVB standard, Serial interface
Output BitRate		1.0~15Mbps continuously adjustable per channel
Control		NMS (Ethernet port, RJ-45), Keyboard + LCD
General Features	Size	482mm×410mm×44mm
	Temperature Range	0~45°C (Operation); -20~80°C (Storage)
	Power	100-240VAC, 50Hz, 25W

ORDER INFORMATION

P/N	Description
CSD-8000	8 in 1 MPEG-2 AVC SD Encoder