



- Exceeds ANSI/TIA/EIA 568-C.2 CAT 6 requirements
- Exceeds ISO/IEC 11801 Class E
- Terminates 4 pair 22 to 24 AWG solid UTP
- Variety of attractive colors
- High-impact ABS 94V-0 Plastic Housing

FEATURES:

- Exceeds TIA 568-C.2 CAT 6 performance specifications
- Fit our angled and flush faceplates on surface boxes
- No punchdown tool needed
- 50u" Gold Plated contacts
- Variety of attractive colors
- Provides both T568A/B color termination schemes
- Best NEXT and low insertion loss for extra ACR
- 47 CFR part 68 (RJ-45)

APPLICATION:

- Horizontal distribution & backbone cabling
- 4/16 Mbps token ring (IEEE 802.5)
- 10/100/1000 BASE-T (IEEE 802.3)
- 155 Mbps
- 100Mbps TP-PMD
- ISDN, ADSL
- Analog & digital voice (VoIP) and video
- Full broadband and baseband video

TECHNICAL DETAILS

FEATURE	
Category	ANSI/TIA-568-C.2 Category 6
Meet	47 CFR part 68
Wiring scheme	T568A or T568B
ELECTRICAL	
Current rating	1.5 (Amps)
Insulation resistance	> 500 (Mega-ohm)
Contact resistance	< 20 (Milli-ohm)
DC resistance	< 0.1 (ohm)
Voltage	< 150 (Vac)
MECHANICAL	
Insertion life	750 (Cycles)
Pulling force	20 (lbs)
Temperature	-20 ~ 68 (°C)
Humidity	10 ~ 90 (% RH)
IDC accept	22-24 Solid Wire (AWG)
PHYSICAL	
Contact blade	Phosphor bronze plated with 50uin thick gold over 100uin thick nickel undercoat
Cable Jacket	PVC

ORDER INFORMATION

PN	DESCRIPTION
CRJ-6203	CAT6 Keystone Jack T568A/B, GRAY
CRJ-6206	CAT6 Keystone Jack T568A/B, WHITE
CRJ-6201	CAT6 Keystone Jack T568A/B, BLACK
CRJ-6204	CAT6 Keystone Jack T568A/B, GREEN
CRJ-6208	CAT6 Keystone Jack T568A/B, BEIGE
CRJ-6210	CAT6 Keystone Jack T568A/B, ORANGE
CRJ-6202	CAT6 Keystone Jack T568A/B, BLUE
CRJ-6205	CAT6 Keystone Jack T568A/B, RED